



E120n Print Cartridge

Printer: E120n

Part Number: 12015SA 12017SR 12016SE 12018SL
12035SA 12037SR 12036SE 12038SL

Declaration of Average Cartridge Yield 2000 standard pages
Yield: Declared yield value in accordance with ISO/IEC 19752

Average 2218
Std Dev 237
90% Lower 2114
Confidence

For questions concerning testing

contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 9-Aug-2005

stop 24-Oct-2005

Number of cartridges in testing 16
Qty. of cartridges used in calculation 16
Shake Procedure 1st shake At fade
2nd shake At fade
Print mode Continuous
Number of printers tested 4
Media used Boise Cascade - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version T120 G6
Operating system Windows 98
Application software Acrobat version 7.01
Test page version 19752_Test_Chart_Ver.200406.pdf

Table with columns: Cartridge testing data, Cartridge, Printer, Temperature (Avg °F, Avg °C, Max °F, Max °C, Min °F, Min °C), Humidity (Avg, Max, Min), Cartridge Yield, Cartridge used in Calculation. Contains 20 rows of test data.

Comments and or exceptions: