



ISO/IEC 19752 Yield Test Report

Part Number: 24015SA,
24035SA

E230, E232, E330, E332 Print Cartridge
Printer: E232

see below for additional part numbers

Declaration of **Average Cartridge Yield 2500 standard pages**
Yield: **Declared yield value in accordance with ISO/IEC 19752**

Average 2919
Std Dev 163
90% Lower Confidence 2834

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

start 11-Jan-2005
stop 12-Jan-2005

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake 2nd shake
Print mode	At fade At fade
Number of printers tested	Continuous
Media used	4
Paper feed orientation	Boise Cascade X-9 - 20# - Letter
Driver version	Short Edge Feed (SEF)
Operating system	9.3
Application software	Windows 2000
Test page version	Adobe Acrobat version 6.01 IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAX043484311	38058XW	74	23	74	23	74	23	50	51	50	3,156	Yes
CAX043502725	3804283	74	23	74	23	74	23	50	51	50	2,951	Yes
CAX043502655	38042BP	74	23	74	23	74	23	50	51	50	2,902	Yes
CAX043513444	3804190	74	23	74	23	74	23	50	51	50	3,007	Yes
CAX043513484	38058XW	74	23	74	23	74	23	50	51	50	2,950	Yes
CAX043484286	3804283	74	23	74	23	74	23	50	51	50	2,988	Yes
CAX043502729	38042BP	74	23	74	23	74	23	50	51	50	2,949	Yes
CAX043502772	3804190	74	23	74	23	74	23	50	51	50	3,173	Yes
CAX043502740	38058XW	74	23	74	23	74	23	50	51	50	2,685	Yes
CAX043513472	3804283	74	23	74	23	74	23	50	51	50	2,840	Yes
CAX043484315	38042BP	74	23	74	23	74	23	50	51	50	2,651	Yes
CAX043502671	3804190	74	23	74	23	74	23	50	51	50	2,772	Yes

Comments and or exceptions:

Also covers:
 12A8300 24018SL 34217HR
 12A8400 24036SE 34237HR
 24016SE 24037SR SWE2500
 24017SR 24038SL