

**E320/E322 High Yield Print Cartridge**

Printer: E320/E322

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>6000</b>	<b>standard pages</b>
<b>Declared yield value in accordance with ISO/IEC 19752</b>			

**Average** 6235  
**Std Dev** 271  
**90% Lower Confidence** 6095

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<b><u>start</u></b>	<b><u>stop</u></b>
<b>Date tested</b>	18-Nov-2004	20-Nov-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At fade 2nd shake At fade
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	7.4.1
Operating system	Windows 2000
Application software	Adobe Acrobat version 6.01
Test page version	IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAD033320549	89073JD	74	74	74	48	49	48	6,216	Y
CAD033331601	89075NB	74	74	74	48	49	48	6,538	Y
CAD033352858	8908T4W	74	74	74	48	49	48	6,198	Y
CAD042320793	8900TQ8	74	74	74	48	49	48	5,886	Y
CAD042321000	89073JD	74	75	74	48	49	47	6,046	Y
CAD033320600	89075NB	74	75	74	48	49	47	6,242	Y
CAD033331584	8908T4W	74	75	74	48	49	47	6,234	Y
CAD033352734	8900TQ8	74	75	74	48	49	47	5,930	Y
CAD033352776	89073JD	74	75	74	48	48	47	6,439	Y
CAD042320497	89075NB	74	75	74	48	48	47	6,571	Y
CAD033320759	8908T4W	74	75	74	48	48	47	5,870	Y
CAD033352438	8900TQ8	74	75	74	48	48	47	6,651	Y

**Comments and or exceptions:**