

E320/E322 Print Cartridge

Printer: E320/E322

Declaration of Yield:	Average Cartridge Yield	3000	standard pages
Declared yield value in accordance with ISO/IEC 19752			

Average 3256
Std Dev 206
90% Lower Confidence 3149

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	17-Nov-2004	1-Dec-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At fade 2nd shake At fade
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	7.4.1
Operating system	Windows 2000
Application software	Adobe Acrobat version 6.01
Test page version	IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAD042091207	89075NB	74	74	74	48	49	48	3,695	Y
CAD041340443	89073JD	74	74	74	48	49	48	3,306	Y
CAD041322727	8908T4W	74	74	74	48	49	48	3,002	Y
CAD041332669	8900TQ8	74	74	74	48	49	48	3,194	Y
CAD041332285	89073JD	74	74	74	48	48	48	3,480	Y
CAD041340451	89075NB	74	74	74	48	48	48	3,495	Y
CAD042092098	8908T4W	74	74	74	48	48	48	3,202	Y
CAD041322482	8900TQ8	74	74	74	48	48	48	3,202	Y
CAD042136208	89073JD	75	75	74	48	48	47	3,058	Y
CAD042138609	8900TQ8	75	75	74	48	48	47	3,185	Y
CAD042136216	89075NB	75	75	74	48	48	47	3,053	Y
CAD042136589	8908T4W	75	75	74	48	48	47	3,197	Y

Comments and or exceptions: