



ISO/IEC 19752 Yield Test Report

Part Number: 34015HA, 34035HA

E330, E332 High Yield Print Cartridge
Printer: E330/E332

see below for additional part numbers

Declaration of Average Cartridge Yield 6000 standard pages
Yield: Declared yield value in accordance with ISO/IEC 19752

Average 6760
Std Dev 438
90% Lower Confidence 6533

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 12-Jan-2005 stop 14-Jan-2005

Number of cartridges in testing 12
Qty. of cartridges used in calculation 12
Shake Procedure 1st shake 2nd shake
Print mode Continuous
Number of printers tested 4
Media used Boise Cascade X-9 - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version 9.3
Operating system Windows 2000
Application software Adobe Acrobat version 6.01
Test page version IS_19752_Testpage_Ver.200406.pdf

Table with 13 columns: Cartridge, Printer, Avg °F, Avg °C, Max °F, Max °C, Min °F, Min °C, Humidity Avg, Humidity Max, Humidity Min, Cartridge Yield, Cartridge used in Calculation. Rows include various cartridge models like CAX043502764 and 38031GP.

Comments and or exceptions:

Also covers:
12A8305 34016HE 34018HL 34217XR
12A8405 34036HE 34038HL 34237XR