



ISO/IEC 19752 Yield Test Report

E350d, E352dn Print Cartridge

Printer: E350d, E352dn

Part Numbers: E250A11A E250A11E E250A11L E250A11P
 E250A21A E250A21E E250A21L E250A21P

Declaration of Yield:	Average Cartridge Yield	3500	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 5101
Std Dev 210
90% Lower Confidence 4971

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** **stop**
 5-Jul-2006 7-Jul-2006

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake 2nd shake
Print mode	At toner low At fade
Number of printers tested	Continuous
Media used	3
Paper feed orientation	Hammermill Tidal - 20# - Letter
Driver version	Short Edge Feed (SEF)
Operating system	E352dn G9
Application software	Window XP
Test page version	Acrobat version 7.0.0 19752_Test_Chart_Ver.200406.pdf

Cartridge testing data:	Printer	Temperature				Humidity			Cartridge Yield	Cartridge used in Calculation		
		Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg			Max	Min
CAS06151CAO	6203DDC	71	22	72	22	70	21	59	60	59	5,110	Yes
CAS061531CC1	6203DD5	71	22	72	22	70	21	59	60	59	4,970	Yes
CAS061531CF9	6203DCP	71	22	72	22	70	21	59	60	59	5,239	Yes
CAS061531CEF	6203DDC	72	22	73	23	72	22	51	53	46	5,139	Yes
CAS061531C80	6203DD5	72	22	73	23	72	22	51	53	46	4,809	Yes
CAS061531CE9	6203DCP	72	22	73	23	72	22	51	53	46	4,961	Yes
CAS061531CF2	6203DDC	72	22	73	23	72	22	53	54	53	5,460	Yes
CAS061531CFD	6203DD5	72	22	73	23	72	22	53	54	53	5,310	Yes
CAS061531D07	6203DCP	72	22	73	23	72	22	53	54	53	4,910	Yes
			-18		-18		-18					No
			-18		-18		-18					No
			-18		-18		-18					No

Comments and or exceptions: