



ISO/IEC 19752 Yield Test Report

E360 2.3k Ship With

Printer: E360

Declaration of Yield:	Average Cartridge Yield	2300	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 2651
Std Dev 223
90% Lower Confidence 2513

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** 31-Jul-2008 **stop** 31-Jul-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake No shake
Print mode	Continuous
Number of printers tested	3
Media used	Tidal Hammermill - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Long Bow Lexmark G9
Operating system	Windows XP SP2
Application software	Acrobat version 7.0.0
Test page version	19752_Test_Chart_Ver200406.pdf

Cartridge testing data:	Printer	Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
		Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS081521450	Mars	72	22	74	23	71	21	44	48	40	3,539	Yes
CAS081521458	Jupiter	72	22	74	23	71	21	44	48	40	3,419	Yes
CAS081521460	Saturn	72	22	74	23	71	21	44	48	40	3,410	Yes
CAS08152145E	Saturn	72	22	74	23	71	21	43	48	40	3,771	Yes
CAS081521453	Mars	72	22	74	23	71	21	43	48	40	3,559	Yes
CAS08152145D	Jupiter	72	22	74	23	71	21	43	48	40	3,519	Yes
CAS081521459	Mars	72	22	73	23	70	21	44	50	40	3,659	Yes
CAS08152145B	Saturn	72	22	73	23	70	21	44	50	40	3,470	Yes
CAS081521463	Jupiter	72	22	73	23	70	21	44	50	40	3,590	Yes

Comments and or exceptions: