



ISO/IEC 19752 Yield Test Report

E360 3.5k Print Cartridge

Printer: E360

Declaration of Yield:	Average Cartridge Yield	3500	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 4039
Std Dev 148
90% Lower Confidence 3947

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** 17-Jun-2008 **stop** 18-Jun-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake No shake
Print mode	Continuous
Number of printers tested	3
Media used	Tidal Hammermill - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Long Bow Lexmark G9
Operating system	Windows XP SP2
Application software	Acrobat version 7.0.0
Test page version	19752_Test_Chart_Ver200406.pdf

Cartridge testing data:	Printer	Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
		Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS081331A58	320024	72	22	74	23	71	22	47	52	43	4,090	Yes
CAS081331A8A	320026	72	22	74	23	71	22	47	52	43	3,900	Yes
CAS081331A6C	320023	72	22	74	23	71	22	47	52	43	4,229	Yes
CAS081331A6F	320024	72	22	74	23	71	22	47	52	43	3,980	Yes
CAS081331A67	320026	72	22	74	23	71	22	47	52	43	4,140	Yes
CAS081331A3C	320023	72	22	74	23	71	22	47	52	43	4,010	Yes
CAS081331A72	320024	72	22	74	23	71	22	47	52	43	3,789	Yes
CAS081331A71	320026	72	22	74	23	71	22	47	52	43	3,979	Yes
CAS081331A68	320023	72	22	74	23	71	22	47	52	43	4,230	Yes

Comments and or exceptions: