



ISO/IEC 19752 Yield Test Report

E450dn Print Cartridge

Printer: E450dn

Part Numbers: E450A11A E450A11E E450A11L E450A11P
E450A21A E450A21E E450A21L E450A21P

Declaration of Yield: **Average Cartridge Yield 6000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 6999
Std Dev 362
90% Lower Confidence 6775

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 12-Jun-2006 stop 15-Jun-2006

Number of cartridges in testing 9
Qty. of cartridges used in calculation 9
Shake Procedure 1st shake At toner low
2nd shake At fade
Print mode Continuous
Number of printers tested 3
Media used Hammermill Tidal - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version E450dn G9
Operating system Window XP
Application software Acrobat version 7.0.0
Test page version 19752_Test_Chart_Ver.200406.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS061406100	6203HCF	73	23	74	24	71	22	53	54	49	6,602	Yes
CAS0614060FA	6203HCK	73	23	74	24	71	22	53	54	49	6,794	Yes
CAS0614060FF	6203HDT	73	23	74	24	71	22	53	54	49	7,770	Yes
CAS061406102	6203HCF	71	22	72	22	71	21	52	54	47	7,350	Yes
CAS061406105	6203HCK	71	22	72	22	71	21	52	54	47	6,911	Yes
CAS0614060FC	6203HDT	71	22	72	22	71	21	52	54	47	6,720	Yes
CAS061406106	6203HCF	72	22	73	23	71	22	52	53	49	6,810	Yes
CAS0614060FD	6203HCK	72	22	73	23	71	22	52	53	49	6,950	Yes
CAS0614060FE	6203HDT	72	22	73	23	71	22	52	53	49	7,088	Yes
			-18		-18		-18					No
			-18		-18		-18					No
			-18		-18		-18					No

Comments and or exceptions: