



Optra M410/M412 Print Cartridge

Printer: Optra M412

Declaration of Yield: Average Cartridge Yield 5000 standard pages Declared yield value in accordance with ISO/IEC 19752

Average 6518
Std Dev 354
90% Lower Confidence 6335

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 22-Nov-2004 stop 29-Nov-2004

Number of cartridges in testing 12
Qty. of cartridges used in calculation 12
Shake Procedure 1st shake 2nd shake At fade At fade
Print mode Continuous
Number of printers tested 4
Media used Boise Cascade X-9 - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version 7.4.1
Operating system Windows 2000
Application software Adobe Acrobat version 6.01
Test page version IS_19752_Testpage_Ver.200406.pdf

Table with 13 columns: Cartridge, Printer, Avg °F, Avg °C, Max °F, Max °C, Min °F, Min °C, Humidity Avg, Humidity Max, Humidity Min, Cartridge Yield, Cartridge used in Calculation. Contains 15 rows of test data.

Comments and or exceptions: