



ISO/IEC 19752 Yield Test Report

MS310 Print Cartridge Printer MS315dn

Declaration of Yield:

Average Cartridge Yield	1,500	Standard Pages
Declared yield in accordance with ISO/IEC 19752		

Average 2,406
Std Dev 72
90% Lower Confidence 2,362

For questions concerning testing contact
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 29-Jul-2013	<u>stop</u> 29-Jul-2013
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	Windows XP SP3 (Version 2002)	
Operating system	Windows XP SP3	
Application software	Acrobat version 9.5.4	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
SCAS122734F0C	451432LM0LHZZ	72 / 22.2	74 / 23.3	70 / 21.1	51	54	48	2,472	Y
SCAS122734F08	451432LM0LHZZ	72 / 22.2	74 / 23.3	70 / 21.1	51	54	48	2,313	Y
SCAS122734F04	451432LM0LHZZ	72 / 22.2	74 / 23.3	70 / 21.1	51	54	48	2,440	Y
SCAS122734F11	451432LM0LHZG	72 / 22.2	74 / 23.3	70 / 21.1	51	54	48	2,356	Y
SCAS122734F14	451432LM0LHZG	72 / 22.2	74 / 23.3	70 / 21.1	51	54	48	2,361	Y
SCAS122734F13	451432LM0LHZG	72 / 22.2	74 / 23.3	70 / 21.1	51	54	48	2,306	Y
SCAS122734F15	451432LM0LHZZ	72 / 22.2	74 / 23.3	70 / 21.1	51	54	48	2,465	Y
SCAS122734EF7	451432LM0LHZZ	72 / 22.2	74 / 23.3	70 / 21.1	51	54	48	2,459	Y
SCAS122734F0E	451432LM0LHZZ	72 / 22.2	74 / 23.3	70 / 21.1	51	54	48	2,483	Y

Comments and or exceptions:

*EOL was determined by the printer calling for the cartridge to be replaced.