



ISO/IEC 19752 Yield Test Report

MS410 Print Cartridge

Printer MS410

Declaration of Yield:	Average Cartridge Yield 1,500 Standard Pages Declared yield in accordance with ISO/IEC 19752
-----------------------	---

Average 2,572
Std Dev 217
90% Lower Confidence 2,438

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	28-Apr-2012	30-Apr-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS610 Series(G3)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS12059711B_S3	4514PTB300139	4514PTB300139	71	73	70	46	53	43	2,693	Y
(S)CAS1205970F8_S3	4514PTB300139	4514PTB300139	71	73	70	46	53	43	2,906	Y
(S)CAS120597110_S3	4514PTB300139	4514PTB300139	71	73	70	46	53	43	2,618	Y
(S)CAS1205970FB_S3	4514PTB300117	4514PTB300117	71	73	70	46	53	43	2,283	Y
(S)CAS1205970C6_S3	4514PTB300117	4514PTB300117	71	73	70	46	53	43	2,372	Y
(S)CAS120597117_S3	4514PTB300117	4514PTB300117	71	73	70	46	53	43	2,290	Y
(S)CAS1205970D4_S3	4514PTB300145	4514PTB300145	71	73	70	46	53	43	2,597	Y
(S)CAS120597114_S3	4514PTB300145	4514PTB300145	71	73	70	46	53	43	2,618	Y
(S)CAS12059710C_S3	4514PTB300145	4514PTB300145	71	73	70	46	53	43	2,775	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.