

LEXMARK ISO/IEC 19752 Yield Test Report

MS610 Ship With Equipment Print Cartridge Printer MS610

Declaration of Yield: **Average Cartridge Yield 6,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 7,565
Std Dev 184
90% Lower Confidence 7,451

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	start	stop
Date Tested	28-Apr-2012	1-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS610 Series (G3)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Yield	Calculation
			Avg (F/C)	(F/C)	(F/C)	Avg	Max	Min		
	(S)CAS120586A02	4514PTB300608	71	73	70	47	54	43	7,692	Y
	(S)CAS120586A7B	4514PTB300608	71	73	70	47	54	43	7,730	Y
	(S)CAS120586A5E	4514PTB300608	71	73	70	47	54	43	7,456	Y
	(S)CAS120586A12	4514PTB300609	71	73	70	47	54	43	7,772	Y
	(S)CAS120586A13	4514PTB300609	71	73	70	47	54	43	7,679	Y
	(S)CAS120586A8C	4514PTB300609	71	73	70	47	54	43	7,690	Y
	(S)CAS120586A01	4514PTB300611	71	73	70	47	54	43	7,444	Y
	(S)CAS120586A7A	4514PTB300611	71	73	70	47	54	43	7,340	Y
	(S)CAS120586A8A	4514PTB300611	71	73	70	47	54	43	7,285	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.