



## ISO/IEC 19752 Yield Test Report

### MS811 Print Cartridge

Printer MS811

Declaration of Yield: 
**Average Cartridge Yield 25,000 Standard Pages**  
**Declared yield in accordance with ISO/IEC 19752**

**Average 28,282**  
**Std Dev 850**  
**90% Lower Confidence 27,755**

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
<b>Date Tested</b>	19-Jul-2012	8-Aug-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 9
Operating system		Windows XP SP3
Application software		Acrobat version 9.1
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
	(S)CAS1219231FF	406312790000Z	72	75	68	48	55	42	28,982	Y
	(S)CAS1219231CB	406312790000Z	72	75	68	48	55	42	29,078	Y
	(S)CAS1219231B3	406312790000Z	72	75	68	48	55	42	28,642	Y
	(S)CAS1219231EF	406312790000Y	72	75	68	48	55	42	27,536	Y
	(S)CAS1219231D8	406312790000Y	72	75	68	48	55	42	26,901	Y
	(S)CAS1219231B6	406312790000Y	72	75	68	48	55	42	27,304	Y
	(S)CAS1219231FD	4063127900085	72	75	68	48	55	42	29,287	Y
	(S)CAS1219231D2	4063127900085	72	75	68	48	55	42	28,581	Y
	(S)CAS121923202	4063127900085	72	75	68	48	55	42	28,227	Y

**Comments and or exceptions:**

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.