



ISO/IEC 19752 Yield Test Report

MS812 Print Cartridge

Printer MS812

Declaration of Yield:	Average Cartridge Yield 10,000 Standard Pages Declared yield in accordance with ISO/IEC 19752
-----------------------	--

Average 10,661
Std Dev 339
90% Lower Confidence 10,451

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>	
Date Tested	4-May-2012	6-May-2012	
Number of cartridges in testing		9	
Qty. of cartridges used in calculation		9	
Shake Procedure			
	1st shake	No Shake	
	2nd shake	No Shake	
Print mode		Continuous	
Number of printers tested		3	
Media used		Orange Paper - 80gsm - A4	
Paper feed orientation		Short Edge Feed (SEF)	
Driver version		Gold 9	
Operating system		Windows XP SP3	
Application software		Acrobat version 9.1	
Test page version		ISO_IEC_19752_2004_Test_Page.pdf	

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS120545DDDF	40631279000BB	74	78	69	40	48	37	10,900	Y	
(S)CAS120545DE8	40631279000BB	74	78	69	40	48	37	10,235	Y	
(S)CAS120545DE0	40631279000BB	74	78	69	40	48	37	10,530	Y	
(S)CAS120545DEE	4063127900043	74	78	69	40	48	37	11,135	Y	
(S)CAS120545DEC	4063127900043	74	78	69	40	48	37	10,570	Y	
(S)CAS120545DF2	4063127900043	74	78	69	40	48	37	11,130	Y	
(S)CAS120545DFF	406312790004K	74	78	69	40	48	37	10,755	Y	
(S)CAS120545DEA	406312790004K	74	78	69	40	48	37	10,320	Y	
(S)CAS120545DD8	406312790004K	74	78	69	40	48	37	10,370	Y	

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.