



ISO/IEC 19752 Yield Test Report

MX710 / MX811 High Yield Print Cartridge Printer MX710 / MX811

Declaration of Yield:	Average Cartridge Yield	25,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 28,282
Std Dev 850
90% Lower Confidence 27,755

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 19-Jul-2012	<u>stop</u> 8-Aug-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 9
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS1219231FF	406312790000Z	72 / 22.2	75 / 23.8	68 / 20	48	55	42	28,982	Y
(S)CAS1219231CB	406312790000Z	72 / 22.2	75 / 23.8	68 / 20	48	55	42	29,078	Y
(S)CAS1219231B3	406312790000Z	72 / 22.2	75 / 23.8	68 / 20	48	55	42	28,642	Y
(S)CAS1219231EF	406312790000Y	72 / 22.2	75 / 23.8	68 / 20	48	55	42	27,536	Y
(S)CAS1219231D8	406312790000Y	72 / 22.2	75 / 23.8	68 / 20	48	55	42	26,901	Y
(S)CAS1219231B6	406312790000Y	72 / 22.2	75 / 23.8	68 / 20	48	55	42	27,304	Y
(S)CAS1219231FD	4063127900085	72 / 22.2	75 / 23.8	68 / 20	48	55	42	29,287	Y
(S)CAS1219231D2	4063127900085	72 / 22.2	75 / 23.8	68 / 20	48	55	42	28,581	Y
(S)CAS121923202	4063127900085	72 / 22.2	75 / 23.8	68 / 20	48	55	42	28,227	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.