

LEXMARK ISO/IEC 19752 Yield Test Report

MX710 / MX811 Print Cartridge
 Printer MX710 / MX811

Declaration of Yield: **Average Cartridge Yield 6,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 6,777
Std Dev 322
90% Lower Confidence 6,577

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	7-May-2012	8-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 9
Operating system		Windows XP SP3
Application software		Acrobat version 9.1
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS120545DF4	406312790000Z	73	78	69	41	48	37	6,546	Y
(S)CAS120545E16	406312790000Z	73	78	69	41	48	37	6,350	Y
(S)CAS120545DFC	406312790000Z	73	78	69	41	48	37	6,703	Y
(S)CAS120545E1B	406312790000Y	73	78	69	41	48	37	6,592	Y
(S)CAS120545E15	406312790000Y	73	78	69	41	48	37	6,856	Y
(S)CAS120545DF3	406312790000Y	73	78	69	41	48	37	6,493	Y
(S)CAS120545E0B	40631279000085	73	78	69	41	48	37	6,988	Y
(S)CAS120545E19	40631279000085	73	78	69	41	48	37	7,174	Y
(S)CAS120545DFE	40631279000085	73	78	69	41	48	37	7,292	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.