

LEXMARK TM ISO/IEC 19752 Yield Test Report

MX711 / MX812 Extra High Yield Print Cartridge Printer MX711 / MX812

Declaration of Yield:

Average Cartridge Yield	45,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752		

Average 49,763
Std Dev 1,390
90% Lower Confidence 48,902

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	13-May-2012	5-Jun-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		B37
Operating system		Windows XP SP3
Application software		Acrobat version 9.1
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
Cartridge	Printer								
(S)CAN1210704C9	746312790009P	72 / 22.2	76 / 24.4	69 / 20.5	44	50	39	50,622	Y
(S)CAN121080374	746312790009P	72 / 22.2	76 / 24.4	69 / 20.5	44	50	39	50,040	Y
(S)CAN1210704DA	746312790009P	72 / 22.2	76 / 24.4	69 / 20.5	44	50	39	52,331	Y
(S)CAN12108037F	746312790008C	72 / 22.2	76 / 24.4	69 / 20.5	44	50	39	48,280	Y
(S)CAN121080375	746312790008C	72 / 22.2	76 / 24.4	69 / 20.5	44	50	39	47,838	Y
(S)CAN1210704D9	746312790008C	72 / 22.2	76 / 24.4	69 / 20.5	44	50	39	50,755	Y
(S)CAN12108037B	746312790009C	72 / 22.2	76 / 24.4	69 / 20.5	44	50	39	49,274	Y
(S)CAN1210704DB	746312790009C	72 / 22.2	76 / 24.4	69 / 20.5	44	50	39	48,820	Y
(S)CAN1210704D8	746312790009C	72 / 22.2	76 / 24.4	69 / 20.5	44	50	39	49,909	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.