

LEXMARK ISO/IEC 19752 Yield Test Report

MX711 / MX812 Print Cartridge
 Printer MX711 / MX812

Declaration of Yield: **Average Cartridge Yield 6,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 7,482
Std Dev 924
90% Lower Confidence 6,909

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	start	stop
Date Tested	10-May-2012	12-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		B37
Operating system		Windows XP SP3
Application software		Acrobat version 9.1
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
	(S)CAS120545E3B	746312790009P	72	75	69	40	44	36	7,755	Y
	(S)CAS120545ED9	746312790009P	72	75	69	40	44	36	9,480	Y
	(S)CAS120545E0C	746312790009P	72	75	69	40	44	36	6,850	Y
	(S)CAS120545E3D	746312790008C	72	75	69	40	44	36	6,795	Y
	(S)CAS120545E2D	746312790008C	72	75	69	40	44	36	7,985	Y
	(S)CAS120545E08	746312790008C	72	75	69	40	44	36	6,900	Y
	(S)CAS120555BCC	746312790009C	72	75	69	40	44	36	8,025	Y
	(S)CAS120545E2C	746312790009C	72	75	69	40	44	36	6,850	Y
	(S)CAS120545E0A	746312790009C	72	75	69	40	44	36	6,700	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.