

LEXMARK TM ISO/IEC 19752 Yield Test Report

MX810 Print Cartridge
Printer MX810

Declaration of Yield:

Average Cartridge Yield	6,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752		

Average 6,748
Std Dev 163
90% Lower Confidence 6,647

For questions concerning testing contact
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	start	stop
Date Tested	7-May-2012	8-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 9
Operating system		Windows XP SP3
Application software		Acrobat version 9.1
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
Cartridge	Printer								
(S)CAS120545DFB	4063127900002	73	78	69	41	48	37	6,863	Y
(S)CAS120545DF8	4063127900002	73	78	69	41	48	37	6,887	Y
(S)CAS120545DF9	4063127900002	73	78	69	41	48	37	6,719	Y
(S)CAS120555B98	4063127900005	73	78	69	41	48	37	6,762	Y
(S)CAS120555B91	4063127900005	73	78	69	41	48	37	6,872	Y
(S)CAS120555B95	4063127900005	73	78	69	41	48	37	6,706	Y
(S)CAS120545E1E	4063127900010	73	78	69	41	48	37	6,401	Y
(S)CAS120545E17	4063127900010	73	78	69	41	48	37	6,617	Y
(S)CAS120545DF7	4063127900010	73	78	69	41	48	37	6,905	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.