



T420 High Yield Print Cartridge

Printer: T420

Declaration of Yield: Average Cartridge Yield 10000 standard pages. Declared yield value in accordance with ISO/IEC 19752

Average 11590, Std Dev 535, 90% Lower Confidence 11313

For questions concerning testing contact:

Lexmark International Inc. 740 West New Circle Rd. Lexington, Ky. 40550 USA Attn: Laser Supplies Product Manager

Date tested start 28-Nov-2004 stop 1-Dec-2004

Number of cartridges in testing 12, Qty. of cartridges used in calculation 12, Shake Procedure 1st shake 2nd shake, Print mode Continuous, Number of printers tested 4, Media used Boise Cascade X-9 - 20# - Letter, Paper feed orientation Short Edge Feed (SEF), Driver version 8.01, Operating system Windows 2000, Application software Adobe Acrobat version 6.01, Test page version IS_19752_Testpage_Ver.200406.pdf

Table with 13 columns: Cartridge, Printer, Avg °F, Avg °C, Max °F, Max °C, Min °F, Min °C, Humidity Avg, Humidity Max, Humidity Min, Cartridge Yield, Cartridge used in Calculation. Rows include various cartridge models like CAD040833059, CAD040947631, etc.

Comments and or exceptions: