



T520/T522 High Yield Print Cartridge

Printer: T520

Declaration of Yield: Average Cartridge Yield 20000 standard pages Declared yield value in accordance with ISO/IEC 19752

Average 21502
Std Dev 538
90% Lower Confidence 21223

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 17-Jan-2005 stop 21-Jan-2005

Number of cartridges in testing 12
Qty. of cartridges used in calculation 12
Shake Procedure 1st shake 2nd shake
At toner low
At toner low
Print mode Continuous
Number of printers tested 4
Media used Boise Cascade X-9 - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version 7.4.1
Operating system Windows 2000
Application software Adobe Acrobat version 5
Test page version Standard\_Testpage\_(PDF\_1.3).pdf

Table with 13 columns: Cartridge, Printer, Avg °F, Avg °C, Max °F, Max °C, Min °F, Min °C, Humidity Avg, Humidity Max, Humidity Min, Cartridge Yield, Cartridge used in Calculation. Rows include various cartridge models like CAX043501FD1D, CAX043501FD4D, etc.

Comments and or exceptions: