



T520/T522 Print Cartridge
Printer: T520

Declaration of Yield:	Average Cartridge Yield	7500	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 7984
Std Dev 354
90% Lower Confidence 7800

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested **start** 29-Oct-2004 **stop** 31-Oct-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	7.4.1
Operating system	Windows 2000
Application software	Adobe Acrobat version 5
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:	Cartridge	Printer	Temperature				Humidity			Cartridge Yield	Cartridge used in Calculation		
			Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg			Max	Min
	CAX041744129	A001871	74	23	75	24	74	23	48	49	48	7,895	Yes
	CAS041330128	A001875	74	23	75	24	74	23	48	49	48	8,304	Yes
	CAS041402019	A001887	74	23	75	24	74	23	48	49	48	7,593	Yes
	CAS041530956	A001990	74	23	75	24	74	23	48	49	48	7,742	Yes
	CAS041530946	A001871	74	23	74	24	74	23	48	48	48	7,854	Yes
	CAX041745543	A001875	74	23	74	24	74	23	48	48	48	7,929	Yes
	CAS041330235	A001887	74	23	74	24	74	23	48	48	48	8,898	Yes
	CAS041402059	A001990	74	23	74	24	74	23	48	48	48	7,976	Yes
	CAS041402079	A001871	74	23	75	24	74	23	48	48	48	7,865	Yes
	CAS041530957	A001875	74	23	75	24	74	23	48	48	48	7,606	Yes
	CAX041744092	A001887	74	23	75	24	74	23	48	48	48	7,956	Yes
	CAS041330204	A001990	74	23	75	24	74	23	48	48	48	8,184	Yes

Comments and or exceptions: