



T630, T632, T634 Print Cartridge

Printer: T634

Declaration of Yield: Average Cartridge Yield 5000 standard pages. Declared yield value in accordance with ISO/IEC 19752

Average 6111, Std Dev 252, 90% Lower Confidence 5981

For questions concerning testing contact:

Lexmark International Inc. 740 West New Circle Rd. Lexington, Ky. 40550 USA Attn: Laser Supplies Product Manager

Date tested start 28-Sep-2004 stop 29-Sep-2004

Number of cartridges in testing 12, Qty. of cartridges used in calculation 12, Shake Procedure 1st shake 2nd shake, Print mode Continuous, Number of printers tested 4, Media used Boise Cascade X-9 - 20# - Letter, Paper feed orientation Short Edge Feed (SEF), Driver version 8.4.0.0, Operating system Windows 2000, Application software Adobe Acrobat version 5.0, Test page version Standard\_Testpage\_(PDF\_1.3).pdf

Table with 13 columns: Cartridge, Printer, Avg °F, Avg °C, Max °F, Max °C, Min °F, Min °C, Humidity Avg, Humidity Max, Humidity Min, Cartridge Yield, Cartridge used in Calculation. Rows include various cartridge models like CAX042028316D, CAX042066315D, etc.

Comments and or exceptions: