



ISO/IEC 19752 Yield Test Report

T640, T642, T644 High Yield Print Cartridge

Printer: T640

Part Number: 64015HA 64017HR 64016HE 64018HL
 64035HA 64037HR 64036HE 64038HL
 64004HA 64004HR 64004HE 64004HL

Declaration of Yield: **Average Cartridge Yield 21000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 23898
Std Dev 925
90% Lower Confidence 23324

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 23-Mar-2005 stop 30-Mar-2005

Number of cartridges in testing 9
 Qty. of cartridges used in calculation 9
 Shake Procedure 1st shake At toner low
 2nd shake At toner low
 Print mode Continuous
 Number of printers tested 3
 Media used Boise Cascade - 20# - Letter
 Paper feed orientation Short Edge Feed (SEF)
 Driver version T640 version 1
 Operating system Windows 2000
 Application software Acrobat version 6.01
 Test page version Down load Free__19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS050559166	PL2-1026-L	75	24	75	24	72	22	51	57	45	24,001	Yes
CAS050559228	PL2-1037-L	75	24	75	24	72	22	51	57	45	24,561	Yes
CAS050559205	PL2-1034-L	75	24	75	24	72	22	51	57	45	24,581	Yes
CAS050559265	PL2-1026-L	75	24	75	24	72	22	51	57	45	22,360	Yes
CAS050559191	PL2-1026-L	75	24	75	24	72	22	51	57	45	24,259	Yes
CAS050559157	PL2-1037-L	75	24	75	24	72	22	51	57	45	25,059	Yes
CAS050559181	PL2-1037-L	75	24	75	24	72	22	51	57	45	24,200	Yes
CAS050559256	PL2-1034-L	75	24	75	24	72	22	51	57	45	22,538	Yes
CAS050559202	PL2-1034-L	74	24	76	24	72	22	45	53	41	23,519	Yes

Comments and or exceptions: