



ISO/IEC 19752 Yield Test Report

T640, T642, T644 Print Cartridge

Printer: T642

Part Number: 64015SA	64017SR	64016SE	64018SL
64035SA	64037SR	64036SE	64038SL

Declaration of Yield:	Average Cartridge Yield	6000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 7761
Std Dev 426
90% Lower Confidence 7497

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	17-Apr-2005	18-Apr-2005

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake 2nd shake
Print mode	Continuous
Number of printers tested	3
Media used	Boise Cascade - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	T642 version 1
Operating system	Windows 2000
Application software	Acrobat version 6.01
Test page version	Down load Free__19752 Test Chart.pdf

Cartridge testing data:	Cartridge	Printer	Temperature				Humidity			Cartridge Yield	Cartridge used in Calculation		
			Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg			Max	Min
	CAS050910450	PL3-104-M	74	23	75	24	73	23	52	55	49	6781	Yes
	CAS050910538	PL3-104-M	74	23	75	24	73	23	52	55	49	7401	Yes
	CAS050910478	PL3-104-M	74	23	75	24	73	23	52	55	49	7701	Yes
	CAS050910474	PL3-107-M	74	23	75	24	73	23	52	55	49	8100	Yes
	CAS050910467	PL3-107-M	74	23	75	24	73	23	52	55	49	7901	Yes
	CAS050910530	PL3-107-M	74	23	75	24	73	23	52	55	49	7921	Yes
	CAS050910526	PL3-110-M	74	23	75	24	73	23	52	55	49	8000	Yes
	CAS050910510	PL3-110-M	74	23	75	24	73	23	52	55	49	8060	Yes
	CAS050910473	PL3-110-M	74	23	75	24	73	23	52	55	49	7981	Yes

Comments and or exceptions: