



**ISO/IEC 19752 Yield Test
Report**

Part Number: 64015HA
64035HA

T640, T642, T644 High Yield Print Cartridge
Printer: T644

see below for additional part numbers

Declaration of Yield:	Average Cartridge Yield	21000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 24527
Std Dev 1551
90% Lower Confidence 23566

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	start	stop
Date tested	23-Mar-2005	31-Mar-2005

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	3
Media used	Boise Cascade - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	T644 version 1
Operating system	Windows 2000
Application software	Acrobat version 6.01
Test page version	Down load Free__19752 Test Chart.pdf

Cartridge testing data:	Printer	Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
		Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS050559216	PL2-1190-H	75	24	75	24	72	22	51	57	45	23641	Yes
CAS050559174	PL2-1190-H	75	24	75	24	72	22	51	57	45	26039	Yes
CAS050559215	PL2-1191-H	75	24	75	24	72	22	51	57	45	27482	Yes
CAS050559178	PL2-1191-H	75	24	75	24	72	22	51	57	45	24820	Yes
CAS050559276	PL2-1192-H	75	24	75	24	72	22	51	57	45	23979	Yes
CAS050559233	PL2-1192-H	75	24	75	24	72	22	51	57	45	24862	Yes
CAS050559193	PL2-1190-H	75	24	76	24	74	23	45	48	41	24560	Yes
CAS050559201	PL2-1191-H	75	24	76	24	74	23	45	48	41	22440	Yes
CAS050559185	PL2-1192-H	74	23	75	24	72	22	48	53	46	22920	Yes

Comments and or exceptions:

also covers:

- 64004HA 64016HE 64036HE
- 64004HE 64017HR 64037HR
- 64004HL 64018HL 64038HL
- 64004HR