



ISO/IEC 19752 Yield Test Report

T652 Ship With

Printer: T652

Declaration of Yield:	Average Cartridge Yield	10000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 11437
Std Dev 209
90% Lower Confidence 11307

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** 5-Aug-2008 **stop** 6-Aug-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal DP - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	T65x version 1
Operating system	Windows 2000
Application software	Acrobat version 7.1.0
Test page version	19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS080801986	PLT1051	73	23	73	23	71	22	56	59	54	11,487	Yes
CAS080801996	PLT1051	72	22	73	23	71	22	59	60	58	11,206	Yes
CAS080801978	PLT1051	73	23	73	23	70	21	57	61	55	11,222	Yes
CAS08080197A	PLT1042	73	23	73	23	71	22	57	60	54	11,695	Yes
CAS08080197F	PLT1042	72	22	73	23	72	22	58	59	57	11,575	Yes
CAS080801980	PLT1042	72	22	73	23	71	21	57	60	56	11,574	Yes
CAS080801979	PLT1040	73	23	73	23	71	22	56	59	54	11,652	Yes
CAS080801964	PLT1040	72	22	73	23	71	22	58	59	57	11,391	Yes
CAS080801991	PLT1040	72	22	73	23	70	21	57	61	56	11,129	Yes

Comments and or exceptions: