



ISO/IEC 19752 Yield Test Report

T654 Ship With

Printer: T654

Declaration of Yield:	Average Cartridge Yield	10000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 10867
Std Dev 439
90% Lower Confidence 10595

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 21-Jul-2008 stop 23-Jul-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal DP - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	T65x version 1
Operating system	Windows 2000
Application software	Acrobat version 7.1.0
Test page version	19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS08080198D	PLT1072	72	22	73	23	70	21	58	60	56	10,286	Yes
CAS08080196E	PLT1072	71	22	72	22	70	21	58	61	55	11,034	Yes
CAS08080195F	PLT1072	71	21	72	22	70	21	56	58	53	11,332	Yes
CAS080801994	PLT1118	72	22	73	23	70	21	58	59	56	10,047	Yes
CAS08080195E	PLT1118	71	22	73	23	70	21	57	61	55	10,686	Yes
CAS080801965	PLT1118	71	22	72	22	70	21	56	58	53	11,090	Yes
CAS080801981	PLT1112	72	22	73	23	70	21	58	59	56	11,064	Yes
CAS08080199E	PLT1112	71	22	72	22	70	21	57	61	55	11,015	Yes
CAS08080197E	PLT1112	71	21	72	22	70	21	56	58	53	11,245	Yes

Comments and or exceptions: