



**ISO/IEC 19752 Yield Test
Report**

T650, T652, T654 Print Cartridge

Printer: T654

Declaration of Yield:	Average Cartridge Yield	7000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 8198
Std Dev 304
90% Lower Confidence 8009

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 18-Jul-2008 stop 19-Jul-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal DP - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	T65x version 1
Operating system	Windows 2000
Application software	Acrobat version 7.1.0
Test page version	19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS080801A0C	PLT1072	72	22	72	22	71	22	56	57	55	8,395	Yes
CAS0808019CD	PLT1072	72	22	72	22	71	22	54	54	53	8,271	Yes
CAS0808019FA	PLT1072	71	21	72	22	70	21	57	58	55	7,873	Yes
CAS080801A02	PLT1118	72	22	72	22	71	22	56	57	54	8,124	Yes
CAS0808019E2	PLT1118	71	22	72	22	70	21	54	58	53	8,676	Yes
CAS0808019DC	PLT1118	71	21	71	22	70	21	57	58	57	7,888	Yes
CAS0808019CA	PLT1112	72	22	72	22	71	22	56	57	54	8,520	Yes
CAS0808019EA	PLT1112	71	22	72	22	70	21	54	58	53	7,803	Yes
CAS0808019AA	PLT1112	71	22	72	22	70	21	57	58	55	8,233	Yes

Comments and or exceptions: