



**ISO/IEC 19752 Yield Test Report**

W850 High Yield Print Cartridge  
Printer: W850

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>35000</b>	<b>standard pages</b>
	<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 39117  
**Std Dev** 1243  
**90% Lower Confidence** 38346

**For questions concerning testing contact:**  
Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

**Date tested**      **start** 14-Jan-2009      **stop** 30-Jan-2009

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake No shake 2nd shake No shake
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal - 20# - Letter
Paper feed orientation	Long Edge Feed (LEF)
Driver version	W850dn Beta 9
Operating system	Window XP
Application software	Acrobat version 7.0.8
Test page version	19752_Test_Chart_Ver.200406_.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
JP-CT200435-89C-1001000319	J-05-19598	73	23	74	23	71	22	49	50	47	38,140	Yes
JP-CT200435-89C-1001000382	J-05-19521	73	23	74	23	71	22	49	50	47	39,940	Yes
JP-CT200435-89C-1001000384	J-05-19698	73	23	74	23	71	22	49	50	47	41,190	Yes
JP-CT200435-89C-1001000387	J-05-19598	72	22	73	23	71	22	49	51	47	38,460	Yes
JP-CT200435-89C-1001000379	J-05-19521	72	22	73	23	71	22	49	51	47	40,090	Yes
JP-CT200435-89C-1001000224	J-05-19698	72	22	73	23	71	22	49	51	47	37,430	Yes
JP-CT200435-89C-1001000222	J-05-19598	72	22	73	23	71	22	49	51	48	39,080	Yes
JP-CT200435-89C-1001000221	J-05-19521	72	22	73	23	71	22	49	51	48	39,880	Yes
JP-CT200435-89C-1001000218	J-05-19698	72	22	73	23	71	22	49	51	48	37,840	Yes

**Comments and or exceptions:**