



X342n Cartridge

Printer: X342n

Declaration of Yield:	Average Cartridge Yield	6000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 8553
Std Dev 285
90% Lower Confidence 8376

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested **start** 21-Mar-2006 **stop** 12-Apr-2006

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At fade 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	X340 XL G2
Operating system	Windows XP
Application software	Acrobat version 7.01
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:	Printer	Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
		Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS060061EA6	68P1028	72	22	73	23	72	22	49	50	48	9,051	Yes
CAS060061EDC	68P1027	72	22	73	23	72	22	49	50	48	8,451	Yes
CAS060061E79	68P1025	72	22	73	23	72	22	49	50	48	8,561	Yes
CAS060061E96	68P1028	74	23	74	23	73	23	44	45	44	8,771	Yes
CAS060061E57	68P1027	74	23	74	23	73	23	44	45	44	8,565	Yes
CAS060061E18	68P1025	74	23	74	23	73	23	44	45	44	8,721	Yes
CAS060061CAF	68P1028	73	23	73	23	73	23	45	48	41	8,291	Yes
CAS060061E7B	68P1027	73	23	73	23	73	23	45	48	41	8,502	Yes
CAS060061E2E	68P1025	73	23	73	23	73	23	45	48	41	8,061	Yes

Comments and or exceptions: