



ISO/IEC 19752 Yield Test Report

X264, X363, X364 Print Cartridge

Printer: X360

Declaration of Yield:	Average Cartridge Yield	3500	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 4213
Std Dev 154
90% Lower Confidence 4118

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** 3-Nov-2008 **stop** 12-Nov-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal MP - 20# - Letter - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Gold 5
Operating system	Windows XP
Application software	Acrobat version 7.0.9
Test page version	19752_Test_Chart_Ver.200406_.PDF

Cartridge testing data:	Printer	Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
		Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAN0829500B5	603110	73	23	74	23	73	23	51	51	50	4,121	Yes
CAN0829500E3	603104	73	23	74	23	73	23	51	51	50	4,349	Yes
CAN0829500BD	603154	73	23	74	23	73	23	51	51	50	4,146	Yes
CAN0829500E9	603110	73	23	74	23	72	22	51	52	50	4,159	Yes
CAN0829500E7	603104	73	23	74	23	72	22	51	52	50	4,141	Yes
CAN0829500BB	603154	73	23	74	23	72	22	51	52	50	4,390	Yes
CAN0829500B8	603110	73	23	73	23	72	22	51	51	50	3,925	Yes
CAN0829500DA	603104	73	23	73	23	72	22	51	51	50	4,316	Yes
CAN0829500E5	603154	73	23	73	23	72	22	51	51	50	4,370	Yes

Comments and or exceptions: