



**ISO/IEC 19752 Yield Test  
Report**

X463, X464, X466 Print Cartridge

Printer: X463

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>3500</b>	<b>standard pages</b>
	<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 4073  
**Std Dev** 106  
**90% Lower Confidence** 4008

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      **start** 6-Jun-2008      **stop** 9-Jun-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Tidal Hammermill - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Long Bow Lexmark G9
Operating system	Windows XP SP2
Application software	Acrobat version 7.0.0
Test page version	19752_Test_Chart_Ver200406.pdf

Cartridge testing data:	Cartridge	Printer	Temperature				Humidity			Cartridge Yield	Cartridge used in Calculation		
			Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg			Max	Min
	CAS081331A6A	Pluto	70	21	71	22	69	21	55	60	52	4,018	Yes
	CAS081331A5A	Neptune	70	21	71	22	69	21	55	60	52	4,069	Yes
	CAS081331A8B	Uranus	70	21	71	22	69	21	55	60	52	4,079	Yes
	CAS081331A62	Neptune	71	22	72	22	69	21	54	56	50	4,079	Yes
	CAS081331A4B	Pluto	71	22	72	22	69	21	54	56	50	3,939	Yes
	CAS081331A88	Uranus	71	22	72	22	69	21	54	56	50	4,108	Yes
	CAS081331A3A	Pluto	71	22	72	22	69	21	54	56	50	4,090	Yes
	CAS081331A61	Neptune	71	22	72	22	69	21	54	56	50	3,969	Yes
	CAS081331A69	Uranus	71	22	72	22	69	21	54	56	50	4,310	Yes

**Comments and or exceptions:**