



X850e/X852e/X854e Print Cartridge

Printer: X852e

Declaration of Yield: Average Cartridge Yield 30000 standard pages Declared yield value in accordance with ISO/IEC 19752

Average 37344
Std Dev 1436
90% Lower Confidence 36600

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 5-Oct-2005 stop 13-Oct-2005

Number of cartridges in testing 12
Qty. of cartridges used in calculation 12
Shake Procedure 1st shake No shake
2nd shake No shake
Print mode Continuous
Number of printers tested 4
Media used Boise Cascade - 20# - Letter
Paper feed orientation Long Edge Feed (LEF)
Driver version X852e Beta 14
Operating system XP Professional 2002 Service Pack 2
Application software Adobe Reader Version 7.0.0
Test page version 19752_Test_Chart_Ver.200406_.pdf

Table with 13 columns: Cartridge, Printer, Avg °F, Avg °C, Max °F, Max °C, Min °F, Min °C, Humidity Avg, Humidity Max, Humidity Min, Cartridge Yield, Cartridge used in Calculation. Contains 14 rows of test data.

Comments and or exceptions: