



X850e/X852e/X854e Print Cartridge

Printer: X854e

Declaration of Yield: Average Cartridge Yield 30000 standard pages Declared yield value in accordance with ISO/IEC 19752

Average 31891
Std Dev 1483
90% Lower Confidence 31080

For questions concerning testing contact: Lexmark International Inc. 740 West New Circle Rd. Lexington, Ky. 40550 USA Attn: Laser Supplies Product Manager

Date tested start 12-Sep-2005 stop 15-Sep-2005

Number of cartridges in testing 11
Qty. of cartridges used in calculation 11
Shake Procedure 1st shake 2nd shake No shake No shake
Print mode Continuous
Number of printers tested 4
Media used Boise Cascade - 20# - Letter
Paper feed orientation Long Edge Feed (LEF)
Driver version X854e Beta 14
Operating system XP Professional 2002 Service Pack 2
Application software Adobe Reader Version 7.0.0
Test page version 19752\_Test\_Chart\_Ver.200406\_.pdf

Table with columns: Cartridge testing data, Cartridge, Printer, Temperature (Avg, Max, Min in °F and °C), Humidity (Avg, Max, Min), Cartridge Yield, Cartridge used in Calculation. Contains 12 rows of test data.

Comments and or exceptions: